### RCP-1500

Standard remote control panel with Joystick type control



The RCP-1500 remote control panel incorporates an LCD display with direct operation switches and a touch panel, which makes it a remote control panel that offers both ease of operation and multi-functionality that compares favorably with the MSU. The iris and master black adjustment block employs joystick type control. Up to four units can be mounted in a 19-inch EIA rack.

## Features

### Touch panel and many direct access switches suitable for various camera operations

This remote control panel is equipped with the control functions required to perform various camera operations enabling the simple and accurate operation of various functions. The operation buttons, adjustment knobs, and other controls are arranged on the panel

# **Technical Specifications**

General	
Power consumption	4 W
Operating temperature	5 °C to 40 °C (41 °F to 104 °F)
Dimensions (W x H x D) (excluding protrusions)	102 × 310 × 125 mm (4 1/8 × 12 1/4 × 5 in)
Mass	1.8 kg (3 lb. 15 oz.)
Power supply	DC 10.5 V to 30 V

# **Compatible Products**

## **High Definition HDC Series**



### HDC-1500R

Multi format HD Camera with fibre interface for Prestige Production



HXC-D70H HD/SD System Camera main unit

according to function and frequency of use. Guard frames are provided around buttons that are vital to the operation and setup of cameras to prevent the buttons from being unintentionally operated

### Ethernet connection capability

It is possible to connect by LAN cable in addition to connecting using CCA-5 cable. Therefore, when setting up a multi-camera control system, not only can a system be built using the CNU-700 as previously, but a system can also be built using a LAN.

### **Direct Scene file control**

Easily access Scene file to support various scene setting.

### Customisable switch and menu.

User's can assign any function to a spare switch and also make their own favourite menu as well.

Input/output connectors	
Ethernet	RJ-45 8-pin (X1)
CCU/CNU	Multi-connector 8-pin, fe- male (x1)
AUX	Multi-connector 8-pin, fe- male (x1)
EXT I/O	D-sub 9-pin, female (x1)



### HXC-D70K

HD/SD System Camera with Full HD 2/3-inch Exmor  $^{\rm TM}$  CMOS Sensors, Viewfinder and Lens



#### HXC-D70L

HD/SD System Camera with Full HD 2/3-inch Exmor™ CMOS Sensors and Viewfinder

### **High Definition HDC Series**



### HDC-1500R

Multi format HD Camera with fibre interface for Prestige Production



#### HXC-D70K

HD/SD System Camera with Full HD 2/3-inch  $\mathsf{Exmor}^{\mathsf{TM}}$  CMOS Sensors, Viewfinder and Lens



HXC-D70H

HD/SD System Camera main unit



### HXC-D70L

HD/SD System Camera with Full HD 2/3-inch Exmor™ CMOS Sensors and Viewfinder

### XDCAM



### PDW-F800

XDCAM HD422 Camcorder



#### PMW-500

XDCAM HD422 Camcorder recording HD material at up to 50Mb/s onto Solid State media



#### PDW-700

XDCAM HD422 Camcorder recording HD material at up to 50Mb/s onto Dual Layer Professional Disc



#### PMW-EX3

A Semi-Shoulder Full-HD Camcorder With SxS PRO Recording, for an Evolving Era of HD

## **XDCAM EX Camcorders**



### PMW-EX3

A Semi-Shoulder Full-HD Camcorder With SxS PRO Recording, for an Evolving Era of HD